

Quality Refrigeration Since 1947



NOVA TM **Products**

Reach-in, Roll-in & Pass-Thru Cabinets & Heated Cabinets



Open Air Merchandisers



Milk Coolers & Milk Cooler Storage



Specialty Freezers



Display Freezers



Ice Crusher

NOVA[™] Reach-in Refrigerators and Freezers are perfect for high-volume applications as the airflow design consistently maintains temperature tolerances. They also boast the largest interior storage space in the industry.

- Refrigerators and freezers
- Glass doors available (refrigerator models only)
- Available in 1, 2 ,or 3 full or half door models
- Top mount refrigeration system
- Microprocessor with digital display
- Stainless steel interior and exterior
- Standard models ship the same day!
- UL and C-UL Safety & UL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
Refrigerators						
NR241	81-1/2"	27-1/2"	35-1/8"	24.1	1/4	115/60/1
NR522	81-1/2"	55"	35-1/8"	51.9	1/3	115/60/1
NR803	81-1/2"	82-1/2"	35-1/8"	79.9	1/2	115/60/1
Freezers						
NF241	81-1/2"	27-1/2"	35-1/8"	24.1	1/2	115/60/1
NF522	81-1/2"	55"	35-1/8"	51.9	3/4	115/60/1
NF803	81-1/2"	82-1/2"	35-1/8"	79.9	1	115/60/1

NOVA[™] Pass-Thru, Roll-Thru, and Roll-In Refrigerators meet multiple demands for performance and provide many flexible configurations to meet your needs.

- Stainless steel interior
- Stainless and galvanized steel exterior
- Pass-thrus available in 1, 2, or 3 solid, glass or half doors
- Roll-ins and roll-thrus available in 1 or 2 doors
- Heavy-duty pivot hinges
- Horizontal work flow pull handles
- Microprocessor with digital display
- UL and C-UL Safety & UL Sanitation; NSF and UL Safety on roll-in models



	Height	Width	Depth	CuFt	HP	Voltage
Pass-Thrus						
PR242	81-1/2"	27-1/2"	38-1/4"	25.6	1/3	115/60/1
PR524	81-1/2"	55"	38-1/4"	55.7	1/2	115/60/1
PR806	81-1/2"	82-1/2"	38-1/4"	85.8	3/4	115/60/1
Roll-ins						
WR331	84-3/4"	31-3/4"	36-3/8"	34.2	1/3	115/60/1
WR722	84-3/4"	63-1/2"	36-3/8"	72.5	1/2	115/60/1
Roll-Thrus						
PWR332	84-3/4"	31-3/4"	39-3/4"	33.0	1/3	115/60/1
PWR724	84-3/4"	63-1/2"	39-3/4"	72.0	1/2	115/60/1

Standard Three Year Parts and Labor, Five Year Compressor Warranties

NOVA[™] Heated Reach-ins, Pass-Thrus and Roll-Thrus provide exacting temperature maintenance to protect your products.

- Stainless steel interior
- Stainless and galvanized steel exterior
- Horizontal work flow handles
- Maintains up to +200°F
- Ducted air distribution
- Digital LED thermometer
- UL and C-UL Safety & UL Sanitation



	Height	Width	Depth	CuFt	Watts	Voltage
Reach-ins						
NW211	81-1/2"	27-1/2"	35-1/8"	22.5	1500	115/60/1
NW482	81-1/2"	55"	35-1/8"	48.8	3000	115/208-230/60/1
Pass-Thrus						
PW252	81-1/2"	27-1/2"	38-1/4"	25.6	1500	115/60/1
PW554	82-3/4"	55"	38-1/4"	55.7	3000	115/208-230/60/1
Roll-Thrus						
PWW332	84-3/4"	31-3/4"	39-3/4"	36.4	1500	115/60/1
PWW724	84-3/4"	63-1/2"	38-3/4"	78.1	3000	115/208-230/60/1

NOVA™ Open Air Merchandisers

NOVA[™] Horizontal Open Air Merchandisers boost sales potential with convenient grab and go access for sandwiches, salads and other items.

- · 24 gauge black painted textured galvanized steel interior and exterior front and top
- Automatic condensate removal system
- LED lighting in canopy
- Electronically controlled monitoring system
- Retractable night curtain
- UL and C-UL Safety & UL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
Merchandisers						
NLHOAM36	46"	35-1/2"	34"	4.6	1/2	115/60/1
NLHOAM48	46"	47-1/2"	34"	6.3	1/2	115/60/1
NLHOAM60	46"	59-1/2"	34"	7.9	3/4	115/60/1
NLHOAM72	46"	71-1/2"	34"	9.6	3/4	115/60/1

NOVA™ Open Air Merchandisers

NOVA[™] Vertical Open Air Merchandisers are available in a wide variety of sizes and a larger pack-out space than many competitive models.

- 24 gauge black painted textured galvanized steel interior and exterior front and top
- Two-position cantilever shelving with price tag molding
- Automatic defrost
- LED lighting in canopy
- · Electronically controlled monitoring system
- Retractable night curtain
- UL and C-UL Safety & UL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
60" Height						
NLVOAM36-60	60"	35-1/2"	34"	13.4	1/2	115/60/1
NLVOAM48-60	60"	47-1/2"	34"	18.2	3/4	115/60/1
NLVOAM60-60	60"	59-1/2"	34"	23.1	1	115/60/1
NLVOAM72-60	60"	71-1/2"	34"	28.0	1	115/60/1
72" Height						
NLVOAM36-72	72"	35-1/2"	34"	17.8	3/4	115/60/1
NLVOAM48-72	72"	47-1/2"	34"	24.2	1	115/60/1
NLVOAM60-72	72"	59-1/2"	34"	30.7	1	208-230/60/1
NLVOAM72-72	72"	71-1/2"	34"	37.1	1	208-230/60/1
79" Height						
NLVOAM36-79	79"	35-1/2"	34"	20.8	3/4	115/60/1
NLVOAM48-79	79"	47-1/2"	34"	28.3	1	115/60/1
NLVOAM60-79	79"	59-1/2"	34"	35.9	1	208-230/60/1
NLVOAM72-79	79"	71-1/2"	34"	43.4	1	208-230/60/1

Standard Three Year Parts and Labor, Five Year Compressor Warranties

NOVA™ Milk Coolers

NOVA[™] Cold Wall Milk Coolers are designed for the most demanding abuse with a reinforced floor and 5-year frame warranty.

- Storage for 8, 12, or 16 cases of milk cartons
- · Corner bumpers on open front and dual access models to protect from damage
- Drop lid(s) that provide easy access to self-serve milk
- Exterior self-service door(s) are stainless steel
- Easy roll locking swivel casters
- Heavy-duty floor racks
- Key locking feature
- UL and C-UL Safety & UL Sanitation



	Height	Width	Depth	Cases	HP	Voltage
Open Front						
AR082	44"	35-3/4"	33-3/4"	8	1/5	115/60/1
AR122	44"	49-3/4"	33-3/4"	12	1/5	115/60/1
AR162	44"	63-3/4"	33-3/4"	16	1/5	115/60/1
Dual Access						
AR084	43-3/4"	35-3/4"	33-3/4"	8	1/5	115/60/1
AR124	43-3/4"	49-3/4"	33-3/4"	12	1/5	115/60/1
AR164	43-3/4"	63-3/4"	33-3/4"	16	1/5	115/60/1
Cooler Storage						
GR422	64-7/8"	63-3/8"	34"	28	1/4	115/60/1

Standard Three Year Parts and Labor, Five Year Compressor Warranties

NOVA[™] Topping Cabinets with a Refrigerated Rail are designed to safely hold all the necessary toppings for sundaes in the NSF Standard 7 rail.

- Stainless steel exterior
- Smooth aluminum cabinet and rail interior liners
- Syrup rail meets NSF Standard 7 requirements and has dedicated temperature controls for the base unit and syrup rail
- UL and C-UL Safety & UL Sanitation



NOVA[™] Topping-Dipping and Storage-Dipping Cabinets provide durability and reliable performance for ice cream serving and storage.

- Stainless steel top
- 24 gauge white painted galvanized steel exterior
- Anti-condensate heaters under stainless top cap (dipping models)
- Leveling legs
- Jars, ladles and pumps are optional (topping-dipping models)
- UL and C-UL Safety & NSF

	Height	Width	Depth	CuFt	HP	Voltage
Refrigerated Rail						
ZF071	47-1/8"	27-1/2"	33-1/8"	7.0	3/8	115/60/1
ZR152	47-1/8"	54"	33-1/8"	15.0	1/4	115/60/1
ZF152	47-1/8"	54"	33-1/8"	15.0	1/2	115/60/1
Topping Dipping						
ZF124	38-1/4"	43"	30-1/8"	12.5	1/4	115/60/1
ZF174	38-1/4"	54"	30-1/8"	16.8	1/3	115/60/1
Dipping						
FF044	34-1/8"	31-7/8"	21-1/8"	5.2	1/4	115/60/1
FF074	34-1/8"	30-5/8"	30-1/8"	7.6	1/4	115/60/1
FF104	34-1/8"	54"	21-1/8"	11.0	1/4	115/60/1
FF114	34-1/8"	43"	30-1/8"	12.5	1/4	115/60/1
FF154	34-1/8"	54"	30-1/8"	17.3	1/3	115/60/1
FF204	34-1/8"	66-5/8"	30-1/8"	22.0	1/3	115/60/1
FF264	34-1/8"	84-5/8"	30-1/8"	29.1	1/3	115/60/1

Standard Two Year Parts and Labor, Five Year Compressor Warranties

NOVA™ Specialty Freezers

NOVA[™] Dipping Display Freezers are available in three configurations to best fit any need.

- Standard profile, low profile glass and curved glass models available
- 24 gauge white painted galvanized steel interior and exterior
- Stainless steel top and attached superstructure with tempered plate glass viewing window
- UL and C-UL Safety & NSF



	Height	Width	Depth	Cans Display/ Storage*	HP	Voltage
Angled Glass						
HF040	50"	26-1/2"	27-3/4"	4/0	1/3	115/60/1
HF100	50"	47-3/4"	27-3/4"	8/4	1/2	115/60/1
HF160	50"	69-1/4"	27-3/4"	12/8	1/2	115/60/1
HF230	50"	90-3/4"	27-3/4"	16/12	3/4	115/60/1
Curved Glass						
HF040	52"	26-1/2"	27-3/4"	4/0	1/3	115/60/1
HF100	52"	47-3/4"	27-3/4"	8/4	1/2	115/60/1
HF160	52"	69-1/4"	27-3/4"	12/8	1/2	115/60/1
HF230	52"	90-3/4"	27-3/4"	16/12	3/4	115/60/1

* 9-1/2" diameter 3 gallon cans

NOVA[™] Curved & Flat Lid Display Freezers are ideal for placing product in high traffic areas for increased impulse sales.

- Standard LED lighting
- Heavy-duty 2" casters add mobility
- Many built-in conveniences such as baskets, floor drains, external thermometers and locks offered as accessories on competitor lines
- Bottom drain with plug
- ETL Safety (US and Canada) & ETL Sanitation



	Height	Width	Depth	CuFt	HP	Voltage
Curved Lid			·			
CTB31-6	33-1/2"	31"	27-3/8"	8.3	1/3	115/60/1
CTB43-9	33-1/2"	41"	27-3/8"	11.5	3/8	115/60/1
CTB52-12	33-1/2"	49"	27-3/8"	14.5	3/8	115/60/1
CTB71-17	33-1/2"	66-1/2"	27-3/8"	20.5	3/4	115/60/1
Flat Lid						
FTB31-6	33"	31"	27"	7.5	1/3	115/60/1
FTB43-9	33"	43"	27"	11.5	1/3	115/60/1
FTB52-12	33"	52"	27"	14.0	1/3	115/60/1
FTB71-17	33"	71"	27"	20.0	2/3	115/60/1



NOVA[™] Ice Crushers provide crushed ice without requiring a specialty ice maker. Its superior capacity is preferrable for high-volume applications.

- Crushes ice to sizes from cube to flake
- Stainless steel exterior
- UL and C-UL Safety & UL Sanitation



	Height	Width	Depth	Tote Pan Capacity (gal.)	HP	Voltage
Ice Crusher						
N14CR	44"	15-1/2"	20"	4.75	1/4	115/60/1

Standard One Year Parts and Labor, Five Year Compressor Warranties



Long-lasting performance.

Maximum versatility.

Superior quality.

Ready to meet the challenge of your foodservice environment.





727 Second Street • Hudson, Wisconsin 54016 800-955-5253 • 715-386-6149 FAX • www.norlake.com



All specifications subject to change without notice. ©2019 Nor-Lake, Inc. A division of Standex International Corp. All rights reserved.